



**Date and design Characteristics**

Character											
1.01	Manufacturer				HELI						
1.02	Model	CPD040-CU6	CPD045-CU6	CPD050-CU6	CPOYD40-TY5	CPOYD45-TY5	CPOYD50-TY5	CPD40-XC3	CPD45-XC3	CPD50-WX5	
1.03	Power type		Diesel		Gasoline/LPG			Diesel			
1.04	Rated capacity	kg	4000	4500	5000	4000	4500	5000	4000	4500	
1.05	Load center	mm					500			5000	
1.06	Driving mode						Seated				
Size											
2.01	Mast height, extended (with backrest, unloaded)	H2	mm				4217				
2.02	max. Fork height	H	mm				3000				
2.03	Mast height, lowered	H1	mm				2275				
2.04	Free lift	H3	mm				150				
2.05	Backrest height (from the fork surface)	H13	mm				1217				
2.06	distance from the seat surface to the overhead guard	H6	mm				980				
2.07	Overall height (overall height)	H4	mm				2270				
2.08	Overall length (fork/without fork)	L/L'	mm	4145/3075	4165/3095	4209/3139	4145/3075	4165/3095	4209/3139		
2.09	Front overhang	L2	mm				555				
2.10	Rear overhang	L3	mm	520	540	584	520	584	540	584	
2.11	Wheel base	L1	mm				2000				
2.12	Traction pin height	H9	mm				385				
2.13	Min. Under clearance (at mast)	H5	mm				175				
2.14	overall width	W1	mm				1480				
2.15	Fork distance (external)(max./min.)	W5	mm				1340/300				
2.16	Tread (front tread/rear tread)	W3/W2	mm				1180/1190				
2.17	Min. Turning radius (inside)	r	mm				220				
2.18	min. Turning radius (outside)	r	mm	2720	2740	2800	2720	2740	2800	2800	
2.19	min. Right angle aisle width	Ra	mm	2480	2500	2550	2480	2500	2550	2550	
2.20	Mast tilting angle (front/rear)	α/β					6°/12°				
2.21	Fork size	L4xWxT	mm				1070x150x50				
Performance											
3.01	Max. Travelling speed (loaded/unloaded)	Km/h		24/25			24/25		19/20	19/20	
3.02	lifting speed (loaded/unloaded)	mm/s		460/520			460/520		360/390	360/390	
3.03	Lowering speed (loaded/ unloaded)	mm/s					<600/>300				
3.04	Traction force (loaded/unloaded)	KN		22/16			25/16		23/15	30/15	
3.05	max. Gradeability(loaded/unloaded)	%		18/20	17/20	16/20	18/20	20/20	18/20	20/20	
Weight											
4.01	Service weight	Kg	6500	6800	7100	6500	6800	7100	6200	6500	6800
4.02	Weight distribution loaded (front/rear)	Kg	8925/1575	9750/1550	10500/1600	8925/1575	9750/1550	10500/1600	8569/1632	9320/1680	10030/1770
4.03	weight distribution unloaded (front/rear)	Kg	2700/3800	2710/4090	2680/4420	2700/3800	2710/4090	2680/4420	2635/3565	2730/3770	2980/3910
Wheels and Tyre											
5.01	Tyre number x:drive wheel (front/rear)				2X2						
5.02	tyre type (front/rear)				Pneumatic tyre						
5.03	tyre model (front)		8.25-15-14PR	300-15-13PR		8.25-15-14PR	300-15-13PR		8.25-15-14PR	300-15-13PR	
5.04	tyre model (rear)					7.00-12-12PR					
5.05	Service brake				powered brake-pedal tyre				vacuum assist -pedal type		
5.06	Parking brake										
Drive and control device											
6.01	Battery (voltage /capacity)	V/Ah		12/120			12/80		24/80		
6.02	Engine manufacturer /model			Cummins 6SF2.8 Tier IV Final			GM 4.3L Gasoline/LPG		Xinchang 4D35G	Wuxi CA4110	
6.03	Engine rated power	KW/rpm		55/2200			Gasoline: 70/2300, LPG: 76.6/2300		48/2300	61/2200	
6.04	Engine rated torque	Nm/rpm		300/1600			Gasoline: 287/1700, LPG: 323.5/1700		230/1600-1800	305/1400-1600	
6.05	Engine cylinder (number-bore *stroke)			4-94-100			6-101.6x88.39		4-98x115	4-110x125	
6.06	engine displacement	L		2.8			4.29418		3.5	4.752	
6.07	Engine fuel tank capacity	L					90				
6.08	Gear number (front/rear)				2-1 powered shift				2-2 manual shift		

Engine Model and Main Specification for Option					
Engine manufacturer /model	Engine rated power / rated speed KW/rpm	Max. torque/speed Nm/rpm	Engine displacement L	Engine cylinder (Number-bore*stroke)	Applied model
Cummins 6SF2.8	55/2200	300/1600	2.8	4-94-100	CPD40-50-CU6
Wuxi CA4110	61/2200	305/1400~1600	4.75	4-110x125	CPD40-50-WX5
GM4.3L Tier IV Certified engine	Gasoline 70/2300 LPG 76.6/2300	Gasoline 287/1700 LPG 323.5/1700	4.29418	6-101.6x88.39	CPD40-50-TY6
Quanchai 4C6-M	48/2300	230/1600-1800	3.47	4-98x115	CPD40-45-OC1



Note: The vertical axis stands for load capacity and the horizontal axis stands for load center which is calculated from the front surface of the forks to the gravity of the standard load. The standard load means a cubic with 1000mm edge length. When mast is tilted forward, using non-standard forks or loading large goods, the load capacity will be reduced. The load capacity of standard mast at different load center can be known from this load chart.

Mast lifting height and fork length table													
Wide view normal mast lifting height (mm)	2600	2700	3000	3300	3500	3700	3750	4000	4250	4500	5000	5500	6000
two stage full free mast lifting height (mm)	2610	2710	3000	3300	3500	3750	4000	4500	5000	5500	6000		
three stage full free mast lifting height (mm)	3920	4350	4500	4700	4800	5000	5400	6000					
fork length (mm)	1070	1220	1370	1520	1670	1820	1970	2120					

Note: Equipments with \* is standard.

INTERNAL COMBUSTION COUNTERBALANCED  
FORKLIFT TRUCK **4-5 ton**

WIDE VIEW MAST												
Mast model	Max. Lifting height	Load capacity (Load center 500mm)(kg)			Height mast retracted (C)(mm)	Tilting angles Forward/backward (°)	Service Weight (kg)					
		CP(CD)40	CP(CD)45	CP(CD)50			CP(CD)40	CP(CD)45	CP(CD)50	CP(C)45	CP(C)50	
M260	2600	4000	4500	5000	2075	6° / 12°	6450	6750	7050	6150	6450	6750
M270	2700	4000	4500	5000	2125	6° / 12°	6475	6775	7075	6175	6475	6775
M300	3000	4000	4500	5000	2275	6° / 12°	6500	6800	7100	6200	6500	6800
M330	3300	4000	4500	5000	2425	6° / 12°	6515	6815	7115	6215	6515	6815
M350	3500	4000	4500	5000	2525	6° / 12°	6525	6825	7125	6225	6525	6825
M370	3700	4000	4500	5000	2625	6° / 12°	6535	6835	7135	6235	6535	6835
M375	3750	4000	4500	5000	2650	6° / 12°	6540	6840	7140	6240	6540	6840
M400	4000	4000	4500	5000	2825	6° / 6°	6560	6850	7150	6250	6550	6850
M425	4250	*3800 *4000	*4300 *4500	*4700 *5000	2950	6° / 6°	6660	6860	7160	6360	6660	6860
M450	4500	*3700 *4000	*4200 *4500	*4500 *5000	3075	6° / 6°	6575	6875	7175	6275	6575	6875
M475	4750	*3500 *4000	*4000 *4200	*4250 *4600	3200	6° / 6°	6590	6890	7190	6290	6590	6890
M500	5000	3200 *3400	*3600 *4000	4000 *4200	3325	6° / 6°	6600	6900	7200	6300	6600	6900
M550	5500	2900 *3100	3200 *3600	3800 *4200	3575	3° / 6°	6630	6930	7230	6330	6630	6930
M600	6000	2600 *2900	3000 *3200	3300 *3600	3825	3° / 6°	6650	6950	7250	6350	6650	6950

Note: \* Refers to the rated capacity with front dual tyre.

WIDE VIEW FULL FREE 2-STAGE MAST														
Mast model	Max. Lifting height	Load capacity (Load center 500mm)(kg)				Free lift (with backrest) (mm)	Full free lift (mm)	Tilting angles Forward/backward (°)	Service Weight (kg)					
		CP(CD)40	CP(CD)45	CP(CD)50	CP(CD)40				CP(CD)45	CP(CD)50	CP(C)45	CP(C)50		
ZM261	2610	4000	4500	5000	2180	960	1380	6° / 12*	6475	6775	7075	6175	6475	6775
ZM271	2710	4000	4500	5000	2230	1010	1430	6° / 12*	6500	6800	7100	6200	6500	6800
ZM300	3000	4000	4500	5000	2375	1155	1575	6° / 12*	6550	6850	7150	6250	6550	6850
ZM330	3300	4000	4500	5000	2525	1305	1725	6° / 12*	6565	6865	7165	6265	6565	6865
ZM350	3500	4000	4500	5000	2625	1405	1825	6° / 12*	6575	6875	7175	6275	6575	6875
ZM375	3750	4000	4500	5000	2750	1530	1950	6° / 12*	6590	6890	7190	6290	6590	6890
ZM400	4000	4000	4500	5000	2875	1655	2075	6° / 6°	6605	6905	7205	6305	6605	6905
ZM450	4500	3700 *4000	4200 *4500	4500 *5000	3125	1905	2326	6° / 6°	6630	6930	7230	6330	6630	6930
ZM500	5000	3400 *3600	4000 *4200	4000 *4500	3375	2155	2576	6° / 6°	6656	6956	7256	6356	6656	6956
ZM550	5500	2900 *3100	3200 *3600	3800 *4200	3625	2405	2826	3° / 6°	6690	6990	7290	6390	6690	6990
ZM600	6000	2600 *2900	3000 *3200	3300 *3600	3875	2655	3076	3° / 6°	6715	7015	7315	6415	6715	7015

Note: (1)Free lift (without backrest) : +380mm;  
(2)\* Refers to the rated capacity with front dual tyre.

WIDE VIEW FULL FREE 3-STAGE MAST														
Mast model	Max. Lifting height	Load capacity (Load center 500mm)(kg)			Height mast retracted (C)(mm)	Free lift (mm)	Full free lift (mm)	Tilting angles Forward/backward (°)	Service Weight (kg)					
		CP(CD)40	CP(CD)45	CP(CD)50					CP(CD)40	CP(CD)45	CP(CD)50	CP(C)45	CP(C)50	
ZSM392	3920	3840 *4000	4350 *4500	4850 *5000	2235	1012	1430	6° / 6°	6700	7000	7300	6400	6700	7000
ZSM435	4350	3500 *3800	4100 *4300	4400 *4800	2380	1157	1575	6° / 6°	6740	7040	7340	6440	6740	7040
ZSM450	4500	3350 *3500	3900 *4200	4200 *4700	2430	1208	1625	6° / 6°	6750	7055	7355	6450	6755	7055
ZSM470	4700	3250 *3400	3800 *4000	4050 *4200	2495	1274	1692	6° / 6°	6775	7075	7375	6475	6775	7075
ZSM480	4800	3150 *3300	3700 *4000	3950 *4100	2530	1307	1725	6° / 6°	6785	7085	7385	6485	6785	7085
ZSM500	5000	3050 *3200	3400 *3800	3800 *4000	2630	1407	1825	6° / 6°	6905	7105	7405	6505	6905	7105
ZSM540	5400	2750 *3000	3100 *3400	3400 *3600	2755	1532	1950	3° / 6°	6845	7145	7445	6545	6845	7145
ZSM600	6000	2400 *2500	2800 *3000	3100 *3400	2995	1772	2190	3° / 6°	6865	7165	7465	6565	6865	7165

Note: (1)Free lift (without backrest) : +365mm;  
(2)\* Refers to the rated capacity with front dual tyre.

HELI



**H series** / HIGH EFFICIENT ENERGY EFFICIENT

**4-5 ton H series**  
INTERNAL COMBUSTION COUNTERBALANCED  
FORKLIFT TRUCK

Standard equipments	Optional equipments	Optional attachments
Standard fork	Cab	Windshield glass
Standard carriage	Warning light	Rear working light
M300 standard mast	Dual air cleaner	Wide carriage
Standard overhead guard	Heater	Control valve (multi throw)
Single air muffler	Fan	High vertical exhaust
Standard purifier	Fire extinguisher	Spark arrested muffler
Control valve (two throw)	Protecting net	Catalyst muffler
Standard pneumatic tyre	Dual tyre	Tilting cylinder boot
Normal seat	Solid tyre	Steering cylinder boot
Driver's tool	Long fork	Two stage free lift mast
	Suspension seat	Three stage free lift mast
		Side shifter
		Fork positioner
		Double side shifter
		Single double pallet handler
		Hinged forks
		Rolator
		Push/Pulls
		Carpet boom
		Load stabilizer
		Turnaloads
		Crane jib
		Fork extension
		Paper roll clamp
		Drum clamp
		Fork clamp
		Block clamp
		Multi-purpose clamp

**ANHUI HELI CO., LTD.**  
ADD: NO.668 Fangxing Street, Economic Development Zone, Heli, P.R.China  
TEL: (86 55 1903639068 636639258 636639358 63662105  
FAX: (86 55 1903639966

WEBSITE: <http://www.helichina.net>  
Email: [hel@helichina.net](mailto:hel@helichina.net)  
\* Details of specifications and equipment are based on information available at time of printing and may change without notice.

AUTHORIZED DEALER

2016/heli copyright

Catalog No.2016-01-A HELI Print

**4-5 ton H series**  
INTERNAL COMBUSTION COUNTERBALANCED  
FORKLIFT TRUCK



**H series** / HIGH EFFICIENT ENERGY EFFICIENT

**HELI**  
LIFTING THE FUTURE

**25 YEARS** TOP1 FORKLIFT MANUFACTURER AND SALES IN CHINA FOR CONSECUTIVE 25 YEARS